



MCRW

MULTI BATTERY CHARGER FOR LIZARD RW/RB SERIES

Multi Battery Charger MCRW is designed for charging RW/RB battery pack, with features including status indicators, secure DC in connector, and BVA protection.

- + FOR UP TO 2 BATTERY PACKS
- + 4 HOURS CHARGING TIME

MIL-STD-810G	OPERATING	STORAGE
TEMPERATURE	0 °C to +45 °C	-40 °C to +70 °C

+ DC-INPUT

12 ~ 32 V_{DC} with BVA

+ DC-CONNECTOR

Standard: 2-pin MIL (200 W AC Adapter)

+ **OPTIONAL:** 3-pin MIL (90 W AC Adapter)

+ BATTERY COMPATIBILITY

RW/RB Battery Pack (BRWB3A)

+ BATTERY PORTS

2

+ CHARGING TIME

approx. 4 hours

+ DIMENSIONS [W×H×D]

129.9 x 94 x 129.9 mm

+ WEIGHT

approx. 325 g

P/N	DESCRIPTION
153079	RW11/RW14/RB14 Multi Battery Charger MCRW (MIL3P)
153097	RW11/RW14/RB14 Multi Battery Charger MCRW (MIL2P)

CUSTOMIZATION:

Need anything not included in the data sheet? roda products are designed to enable customization to your specific program requirements. Please contact your roda sales team member to find the best solution for your requirements.

roda computer GmbH reserves the right to change without notice the information.

roda
RUGGED IT & ELECTRONICS